

M A T E R I A L   S A F E T Y   D A T A   S H E E T

PRODUCT NAME: POOLPOXY HI-BILD - PART A  
PRODUCT CODE: 45-408 BAJA BEIGE

HMIS CODES: H F R P  
2\*3 1

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING  
ADDRESS : 3150 E. PICO BLVD.  
LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300      DATE PRINTED : 6/11/2010  
INFORMATION PHONE : (800) 544-1998      NAME OF PREPARER :

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG	WEIGHT @TEMP(F)	PERCENT
DIGLYCIDYL ETHER OF BISPHENOL A HOMOPOLYMER OSHA PEL: NE, ACGIH TLV: NE	25085-99-8	NA	NA	23
POLYISOCYANATE OSHA PEL: NE, ACGIH TLV: NE	PROPRIETARY			9
TITANIUM DIOXIDE (as total nuisance dust) OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3	13463-67-7	NA	NA	9
~ XYLENE (MIXED ISOMERS) OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	6.1	68	7.33
IRON OXIDE HYDRATE (as total nuisance dust) OSHA PEL: 15 mg/m3, ACGIH TLV: 10 mg/m3	51274-00-1	NA	NA	5
~ METHYL ISOBUTYL KETONE OSHA PEL: 100 ppm, ACGIH TLV: 50 ppm	108-10-1	14.5	68	2.04
~ ETHYL BENZENE OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	100-41-4	10	68	1.41
LIGHT AROMATIC SOLVENT NAPHTHA OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	64742-95-6	3	68	1.3
n-BUTYL ACETATE ACGIH TLV: 150 ppm	123-86-4	8.4	68	1
~ 4-NONY;-PHENOL OSHA PEL: NE, ACGIH TLV: NE	84852-15-3			0.28
~ TOLUENE OSHA PEL: 200 ppm, ACGIH TLV: 100 ppm	108-88-3	21.8	68	0.09
PROPYLENE GLYCOL METHYL ETHER ACETATE OSHA PEL: N/E, ACGIH TLV: N/E	108-65-6	3.7	68	0.1

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 230 - 300	DENSITY: 12.85 lb/gal
VAPOR DENSITY: HEAVIER THAN AIR	SPECIFIC GRAVITY (H2O=1): 1.54
COATING V.O.C.: 1.72 lb/gal	MATERIAL V.O.C.: 1.72 lb/gal
COATING V.O.C.: 206 g/l	MATERIAL V.O.C.: 206 g/l

SOLUBILITY IN WATER: Negligible                      EVAPORATION RATE: SLOWER THAN ETHER  
APPEARANCE AND ODOR: Beige liquid with a mild odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): 40                              METHOD USED: TCC  
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 0                      UPPER: 8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

Wear self-contained breathing equipment in confined areas to avoid inhalation of smoke or fumes. Water should be used to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, sparks, electrical equipment and open flames. Vapors formed by this product may travel and be ignited by sources distant from the handling or use point.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Sparks, flames, excessive heat, poor ventilation

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Its use in poorly ventilated areas can cause nausea, headache and dizziness.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Short-term contact will result in eye irritation. Prolonged and repeated contact can cause a drying of the skin and irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause skin irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse health effects from ingestion may include irritation of the throat and stomach lining. Not expected to be acutely toxic by ingestion.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye and skin irritation, nausea, headache and dizziness.

Chronic: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No  
This material contains ethylbenzene which is classified as "possibly  
carcinogenic to humans" (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
Pre-existing eye, skin and respiratory disorders may be aggravated.

#### EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN  
IF BREATHING IS DIFFICULT. EYE & SKIN CONTACT: FLUSH EYES IMMEDIATELY WITH  
LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP  
AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. INGESTION: IF SWALLOWED,  
DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

#### ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

##### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL (SAND,  
VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA  
OF SPILL WITH WATER.

##### WASTE DISPOSAL METHOD

Incinerate under safe conditions or dispose of in accordance with local, state  
and federal regulations.

##### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

FLAMMABLE! Keep away from heat, sparks and open flame. Avoid breathing vapors.  
Keep containers tightly closed. Keep away from children.

##### OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin.

#### ===== SECTION VIII - CONTROL MEASURES =====

##### RESPIRATORY PROTECTION

All purpose canister mask or air supplied mask, if TLV limits are exceeded.

##### VENTILATION

Local exhaust at point of use in closed spaces.

##### PROTECTIVE GLOVES

Chemical resistant gloves

##### EYE PROTECTION

Safety glasses

##### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

##### WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking  
areas only.

=====  
SECTION IX - TRANSPORT INFORMATION  
=====

DOT (GROUND)

1.3 gallons (5 liters) or less:  
UN1263,Paint,3,PGII, "Ltd. Qty."Greater than 1.3 gallons (5 liters):  
UN1263, Paint,3,PGII

AIR

UN1263,Paint,3,PGII

=====  
SECTION X - REGULATORY INFORMATION  
=====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Toluene -

This product contains a chemical known to the State of California to cause cancer.

Contains: Ethylbenzene -

=====  
SECTION XI - DISCLAIMER  
=====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.