

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: PROPOXY - PART B
PRODUCT CODE: 46-402 BAHAMA BLUE

HMIS CODES: H F R P
2*1 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING
ADDRESS : 3150 E. PICO BLVD.
LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 10/28/2011
INFORMATION PHONE : (800) 544-1998 NAME OF PREPARER :

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG	@TEMP(F)
TITANIUM DIOXIDE (as total nuisance dust) OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3	13463-67-7	NA	NA
EPOXY RESIN/ POLYAMINE ADDUCT OSHA PEL: NE, ACGIH TLV: NE	PROPRIETARY	1.3	68
~ ETHYLENE GLYCOL MONOPROPYL ETHER OSHA PEL: N/E, ACGIH TLV: N/E	2807-30-9	1.16	68
SILICA,SILICONE DIOXIDE OSHA PEL: 20 MPPCF, ACGIH TLV: 20 MPPCF	7631-86-9	NA	NA
ALUMINUM HYDROXIDE OSHA PEL: NE, ACGIH TLV: NE	21645-51-2		
ACETIC ACID OSHA PEL: 10 ppm, ACGIH TLV: 10 ppm	64-19-7	11.4	68

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 245 - 301 DENSITY: 14.6 lb/gl
VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.75
COATING V.O.C.: 1.99 lb/gl MATERIAL V.O.C.: 1.22 lb/gl
COATING V.O.C.: 238 g/l MATERIAL V.O.C.: 146 g/l
SOLUBILITY IN WATER: Soluble EVAPORATION RATE: SLOWER THAN ETHER
APPEARANCE AND ODOR: Blue liquid with slight vinegar odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): >200 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 0 UPPER: 15.8

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES
Do not enter fire area without proper protection. Fight fire from safe distance

location. Heat may build pressure closed containers, spreading fire, increasing risk of burns. Notify authorities if liquid enters sewer/public waters.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, sparks, electrical equipment and open flames. Vapors formed by this product may travel and be ignited by sources distant from the handling or use point.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

None known

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause nasal and respiratory irritation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Short-term contact will result in eye irritation. Prolonged and repeated contact can cause a drying of the skin and irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause skin irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse health effects from ingestion may include respiratory irritation, nausea and vomiting. Not expected to be acutely toxic by ingestion.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, skin and respiratory tract irritation.

Chronic: Prolonged or repeated exposure, as with clothing wet with product, may cause slight irritation.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated. Persons with skin or respiratory tract allergies may develop increased symptoms when exposed to this material.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. EYE AND SKIN CONTACT: FLUSH EYES WITH WATER FOR AT

LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA OF SPILL WITH WATER.

WASTE DISPOSAL METHOD

Incinerate or dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP FROM FREEZING! Close container after each use. Keep away from children.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin.

===== SECTION VIII - CONTROL MEASURES =====

VENTILATION

Local exhaust at point of use in closed spaces.

RESPIRATORY PROTECTION

Provide exhaust ventilation to keep the airborne concentrations of vapors below their respective threshold limit value. If workplace exposure limit(s) of product or any component is exceeded, a NIOSH-approved respirator is advised in absence of proper environmental control.

PROTECTIVE GLOVES

Impermeable chemical handling gloves for skin protection.

EYE PROTECTION

Safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - TRANSPORT INFORMATION =====

DOT (GROUND)

Not regulated

AIR

Not regulated

===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

None

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.