

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: DECKGARD
PRODUCT CODE: 47-708 SAHARA TAN

HMIS CODES: H F R P
1*1 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING
ADDRESS : 3150 E. PICO BLVD.
LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 11/3/2011
INFORMATION PHONE : (323) 261-8114 NAME OF PREPARER :

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	
		mmHG	@TEMP(F)
TITANIUM DIOXIDE (as total nuisance dust) OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3	13463-67-7	NA	NA
TRIME-1,3-PENTANEDIOL, MONOISOBUTYRATE OSHA PEL: NE, ACGIH TLV: NE	25265-77-4	.01	68
~ DIETHYLENE GLYCOL MONOMETHYL ETHER OSHA PEL: N/E, ACGIH TLV: N/E	111-77-3	.1	68
~ 2-BUTOXYETHANOL,ETHYLENE GLYCOL BUTYL ETHER OSHA PEL: 50 ppm, ACGIH TLV: 25 ppm, OTHER: N/E	111-76-2	.78	68
CARBON BLACK(as unbound particles of carbon) ACGIH TLV: 3.5 mg/m3	1333-86-4	NA	NA

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 195 - 471	DENSITY: 10.01 lb/gl
VAPOR DENSITY: HEAVIER THAN AIR	SPECIFIC GRAVITY (H2O=1): 1.2
COATING V.O.C.: 0.79 lb/gl	MATERIAL V.O.C.: 0.26 lb/gl
COATING V.O.C.: 94 g/l	MATERIAL V.O.C.: 31 g/l
SOLUBILITY IN WATER: Soluble	EVAPORATION RATE: SLOWER THAN ETHER
APPEARANCE AND ODOR: Tan liquid with mild odor	

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): >200 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 0 UPPER: 10.6

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
Do not enter fire area without proper protection. Fight fire from safe distance location. Heat may build pressure closed containers, spreading fire, increasing risk of burns. Notify authorities if liquid enters sewer/public waters.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Material will not sustain combustion unless water has evaporated. Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat and open flames

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May result in irritation of the nose, throat and respiratory tract.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: May cause irritation to both.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Maybe harmful if swallowed.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, nose, respiratory tract and skin irritation, headache, dizziness and nausea. Chronic: Prolonged and repeated exposure may cause injury to bone marrow, blood cells, kidney, liver and testes.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No

This material contains carbon black, which is classified as a possible carcinogen for humans (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS.

WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from heat, sparks and open flames. Keep containers tightly closed when not in use. Use with adequate ventilation.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

=====
SECTION VIII - CONTROL MEASURES

VENTILATION

Adequate volume and pattern to keep air contaminant concentration below current applicable OSHA or ACGIH TLV limits.

RESPIRATORY PROTECTION

Provide exhaust ventilation to keep the airborne concentrations of vapors below their respective threshold limit value. If workplace exposure limit(s) of product or any component is exceeded, a NIOSH-approved respirator is advised in absence of proper environmental control.

PROTECTIVE GLOVES

Impermeable chemical handling gloves for skin protection.

EYE PROTECTION

Safety glasses with side shields or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

=====
SECTION IX - TRANSPORT INFORMATION

DOT (GROUND)

Not regulated

AIR

Not regulated

=====
SECTION X - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause cancer.

Contains: Carbon Black -

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.